











The bestseller with high performance

The Kubota 18,5 kW diesel engine and the infeed aperture of 240 x 200 mm ensure that this machine can rightly be called the **JENSEN** best seller.

This chipper combines excellent performance with a particularly compact construction.

200 mm

A540

A540 The most powerful bestseller

Technical details	A540
Max. capacity:	200 mm
Feed roller aperture:	240 x 200 mm
Engine:	Kubota
Output:	18,5 kW
Diameter flywheel:	650 mm
Thickness flywheel:	30 mm
RPM flywheel:	1.200 RPM
Chip size:	5 - 20 mm (hydr. adjustable)
Infeed:	hydraulic motor / gear box
Hopper (w x h):	1.000 x 800 mm
Hydraulic tank:	28
Chassis:	80 km/h (single axle / tandem)
Tires:	175R13C / 185R14C (turntable
Fuel tank capacity:	30 / 45 (turntable)
Dimensions (l x w):	3.530 x 1.480 mm
Working height:	600 mm
Transport height:	2.320 mm
Weight:	approx. 1.200 / 1.450 kg
Turntable:	optional
Capacity:	approx. 15 m³/h

Technical details PTO chipper (540 or 1.000 RPM)		
Required power:	30 kW	
Dimensions:	1.710 x 1.260 mm	
Height with exhaust chute:	2.250 mm	
Weight:	750 kg	
Wheeled chassis:	single axle (25 or 80 km/h)	



This model is also available with turntable. The A540 is our bestseller with high performance and industry leading productivity for the most demanding projects.



System













Galvanized chassis

Chute 360° rototable

Central greasing point V-belt tensioner

Automatic

ECS